



PROVNINGSINTYG (3.1) - Kemisk analys
KVALITETSINTYG(2.2) - Mekaniska egenskaper/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2021-10-22

Certifikat nummer/Cert no:

EC26597048 rev. 0

Vårt ordernr/Our order: 0100375484
Vår referens/Our ref: HYBRIS PRD account
Kundnummer/Cust no: SEB00768
Kundorderdatum/Your date: 20211022

Ert ordernr/Your order: 655875
Er referens/Your ref:
Ert faxnummer/Your fax:
Ert e-post/Your e-mail:

Faktureringsadress/Invoice address

IP INDUSTRIIPARTNER AB
GUSTAFSVÄGEN 13B
633 46 ESKILSTUNA
Sweden

Mottagare av certifikat/Cert receiver

Leveransadress/Delivery address

IP INDUSTRIIPARTNER AB
GUSTAFSVÄGEN 13B
633 46 ESKILSTUNA
Sweden

LEVERANS/DELIVERY

Lotnummer/Lot no:

SFV3410726

Kvantitet/Quantity:

10.2 KGM

PRODUKT/PRODUCT

Varumärke/Brand: ESAB
Beskrivning/Desc: OK 48.00 2.5x350mm 1/2 VP
Artikelnummer/Item no: 48002530G0

KLASSIFICERINGAR/CLASSIFICATIONS

SFA/AWS A5.1: E7018 H4 R
EN ISO 2560-A: E 42 4 B 42 H5

MEKANISKA EGENSKAPER/MECHANICAL PROPS

Typiska data/Typical data: acc to EN 10204 - 2.2

Standard/Standard:

Hjälpmedel/Auxiliary:

Tillstånd/Condition:

DRAGPROV/TENSILE

<u>ReL</u>	<u>Rm</u>	<u>A5</u>
475 MPa	565 MPa	29 %

SLAGPROV/IMPACT

<u>Temp</u>	-30 °C	-40 °C
<u>KV</u>	130 J	115 J

KOMMENTARER/COMMENTS

Tested according to NACE TM0177 and TM0284.

Produkten levereras under ett QA program som uppfyller EN ISO 9001-standard.

Detta intyg är elektroniskt uppbyggt och är giltigt utan underskrift.

Vänligen ställ eventuella frågor till:

ESAB Sverige AB, Lindholmsallén 9, Box 8004, 402 77 Göteborg, Phone:+46 31-50 95 00

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.

This certificate is produced electronically and is valid without signature.

Please refer any queries to: (see above)

Validering - Kemisk analys/Validation - Chemical Analysis

Pál Dranka

Quality Assurance Manager

Validering - annat/Validation - Others

J-P Ernout

Product Manager